

## SPRAY FOAM INSTALLATION TERMS

As consideration for being allowed to purchase products manufactured by Demilec (USA), Inc. ("<u>Demilec</u>) from a Demilec Authorized Distributor, the entity below signing this document ("<u>Installer</u>") agrees to abide by these Spray Foam Installation Terms ("<u>Installation Terms</u>") with regard to all spray foam insulation products received from a Demilec Authorized Distributor or Demilec.

## SPFA CERTIFICATION

All of Installer's personnel who handle or install spray polyurethane foam manufactured by Demilec must be certified under the SPFA Professional Certification Program at the appropriate level (SPF Assistant, SPF Insulation Installer, SPF Insulation Master Installer, or SPF Insulation Project Manager) prior to handling or installing any spray polyurethane product manufactured by Demilec. More information on the SPFA Professional Certification Program can be found at <a href="https://www.sprayfoam.org">www.sprayfoam.org</a>. The prerequisite for SPFA's Professional Certification Program is the High Pressure SPF Chemical Health and Safety Training, which can be completed online at <a href="https://www.spraypolyurethane.org">www.spraypolyurethane.org</a>.

## PRODUCT SAFETY AND INSTALLATION

Installer is responsible for the safe application and installation of all products purchased from a Demilec Authorized Distributor or Demilec. In furtherance of this obligation, Installer agrees to:

- A. Provide and maintain spray equipment to process and apply Demilec spray foam insulation systems in accordance with the Demilec **Product Application Guides** and **Technical Data Sheets**.
- B. Apply Demilec spray foam in accordance with The Center For Polyurethane Industry's **Guidance on Best Practices for the Installation of Spray Polyurethane Foam** and in accordance with SPFA Professional Certification training.
- C. Comply with all current product labels, Safety Data Sheets, Technical Data Sheets, and ICC-ESR Reports.
- D. Provide and use workspace ventilation during and after the spray process according to Guidance on Best Practices for the Installation of Spray Polyurethane Foam.
- E. Adhere to the Demilec Flushing Procedure.
- F. Never mix A-side Iso, also known as Isocyanate and A-PMDI, with water.
- G. Abide by the minimum and maximum thicknesses and temperature requirements designated on the **Technical Data Sheets** for Demilec spray foam products.
- H. Keep accurate records of jobsite activity and information in accordance with Guidance on Best Practices for the Installation of Spray Polyurethane Foam.
- I. Comply with all Occupational Safety Hazard Administration (OSHA) and National Institute for Occupational Safety and Health (NIOSH) regulations related to spray polyurethane foam application including providing appropriate personal protective equipment for all personnel on the jobsite.
- J. Comply with applicable laws, regulations, ordinances, and building codes.
- K. Train personnel to comply with the requirements set forth in this Agreement.

Installer may access the documents referenced in bold above at Demilec's website <a href="www.demilec.com">www.demilec.com</a>. Your Demilec Authorized Distributor will also provide a physical copy of any document referenced herein upon Installer's written request. The documents, guides, guidelines, standards, and links referred to herein (including all documents in bold above) shall be incorporated herein by reference, and as an integral part of this document, to the same extent as if they were set forth verbatim herein.

## INSURANCE

INS

Installer shall keep and maintain at Installer's sole cost and expense comprehensive general liability, broad form property damage and personal injury insurance with coverage to include premises operations, product liability, completed operations, hazard, contractual liability (specifically insuring the liability assumed under this document) with minimum limits of liability of \$1,000,000 per occurrence and \$2,000,000 in the aggregate, on an occurrence form basis. Such insurance shall be issued by a company having an A.M. Best rating of A-VIII or higher. Installer shall provide proof of such insurance upon request from either the Demilec Authorized Distributor or Demilec.

STALLER INFORM	ATION	Control Section Control	
Name:			
Address:			
Contact Person:		E-mail:	
Telephone:		Fax:	
	Signature:		Date: