

Printing date 02/02/2016 Reviewed on 02/02/2015

1 Identification

· Product identifier

· Trade name: Premicote FG White

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Accella Polyurethane Systems, LLC 1255 Kennestone Circle. Suite 200 Marietta, GA 30066 USA

www.premiumspray.com

· Information department: EH&S Department

· Emergency telephone number:

During normal operating hours: (770) 528-9556

ChemTrec: (800) 424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



Health hazard

Carc. 1A H350 May cause cancer.



Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Eye Irrit. 2B H320 Causes eye irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

titanium dioxide

chlorothalonil (ISO)

Distillates (petroleum), solvent-dewaxed heavy paraffinic Distillates (petroleum), solvent-refined heavy paraffinic

· Hazard statements

Causes skin and eye irritation.

May cause an allergic skin reaction.

May cause cancer.

(Contd. on page 2)



Printing date 02/02/2016 Reviewed on 02/02/2015

Trade name: Premicote FG White

(Contd. of page 1)

· Precautionary statements

In case of inadequate ventilation wear respiratory protection.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves/protective clothing/eye protection/face protection.

Avoid release to the environment.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

In case of fire: Use for extinction: CO2, sand, extinguishing powder.

In case of fire: Use for extinction: Water spray.

IF ON SKIN: Wash with plenty of water.

Collect spillage.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1Fire = 0

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 1Fire = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)



rinting date 02/02/2016 Reviewed on 02/02/2015

Trade name: Premicote FG White

))	Contd. of pag
Dangerous	components:	
21645-51-2	aluminium hydroxide	7-13
	Skin Irrit. 2, H315; Eye Irrit. 2B, H320	
13463-67-7	titanium dioxide	5-10
	Carc. 2, H351	
1314-13-2	zinc oxide	1-59
	Skin Irrit. 2, H315; Eye Irrit. 2B, H320	
57-55-6	propane-1,2-diol	≤ 1.0
	Acute Tox. 4, H302	
1897-45-6	chlorothalonil (ISO)	≤ 1.0
	Acute Tox. 2, H330; Carc. 2, H351; Eye Dam. 1, H318; Skin Sens. 1, H317; STOT SE 3, H335	
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic	≤ 1.0
	Carc. 1B, H350	
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic	≤ 1.0
	Carc. 1B, H350	
119-61-9	benzophenone	≤ 1.0
	Carc. 2, H351	
14808-60-7	Quartz (SiO2)	≤ 1.0
	Carc. 1A, H350	
Non-Hazara	dous Components	·
1	Acrylic polymer(s)	10-30
7732-18-5	water, distilled, conductivity or of similar purity	15-40

4 First-aid measures

- · Description of first aid measures
- General information:

Symptoms of exposure may occur after several hours; therefore medical observation for at least 48 hours after exposure.

First Aid responders should pay attention to self-protection and use the recommended protective clothing. If potential for exposure exists refer to Section 8 for specific personal protective quipment.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.



Printing date 02/02/2016 Reviewed on 02/02/2015

Trade name: Premicote FG White

(Contd. of page 3)

5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment:

Mouth respiratory protective device.

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. PVC boots, gloves, safety helmet and protective clothing should be worn.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Isolate area. Keep unnecessary and unprotected personnel from entering the area. Spilled material may cause slipping hazard. Refer to Section 7, Handling, for additional precautionary measures. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

· Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

- · Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

- Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Storage Period: 6 months Storage Temp: 15-35 ℃

· Specific end use(s) No further relevant information available.



Printing date 02/02/2016 Reviewed on 02/02/2015

Trade name: Premicote FG White

(Contd. of page 4)

8 Exposure controls/personal protection

- · Control parameters
- · Components with limit values that require monitoring at the workplace:

57-55-6 propane-1,2-diol

WEEL Long-term value: 10 mg/m³

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

· Breathing equipment:

In case of brief exposure at low atmospheric levels use an approved air-purifying respiratory equiped with an organic vapor sorbent and a particle filter. In case of intensive or longer exposure use a positive pressure air-supplying respirator (air line or self-contained breathing apparatus).

Protection of hands:



Protective gloves

The workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

· Material of gloves

Use chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and microorganisms. Examples of preferred glove barrier materials include: Butyl rubber, Polyethylene, EVAL, Neoprene, Nitrile, Viton. When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher is recommended.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed chemical goggles consistent with EN 166 or equivalent. Wear a face-shield which allows use of chemical goggles, or wear full-face respirator to protect face and eyes when there is any likelyhood of splashes.

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

Color: According to product specification

(Contd. on page 6)



inting date 02/02/2016 Reviewed on 02/02/2015

Trade name: Premicote FG White

		(Contd. of page
· Odor:	Ammonia-like	
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	>100 °C (>212 °F)	
· Flash point:	Not applicable.	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:		
Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapor pressure:	Not determined.	
· Density:	Not determined.	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wat	ter): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
VOC content:	<50 g/liter	
Solids content:	65 % (by weight)	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability This product is stable at recommended storage conditions (See Section 7).
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.



Printing date 02/02/2016 Reviewed on 02/02/2015

Trade name: Premicote FG White

(Contd. of page 6)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50	· LD/LC50 values that are relevant for classification:					
1314-13-2	1314-13-2 zinc oxide					
Oral	LD50	> 5000 mg/kg (rat)				
1897-45-6	1897-45-6 chlorothalonil (ISO)					
Oral	LD50	>10000 mg/kg (rat)				
Inhalative	LC50/4 h	.10 mg/l (rat)				

- · Primary irritant effect:
- on the skin: Irritating effect.
- on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Carcinogenic.

· Carcinogenic categories

· IARC (Intern	ational Agency for Research on Cancer)		
13463-67-7	titanium dioxide		
1897-45-6	chlorothalonil (ISO)		
112926-00-8	Precipitated silica (Silica-Amorphous)		
119-61-9	benzophenone		
14808-60-7	Quartz (SiO2)		
· NTP (Nation	al Toxicology Program)		
14808-60-7	Quartz (SiO2)		
· OSHA-Ca (O	· OSHA-Ca (Occupational Safety & Health Administration)		

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

(Contd. on page 8)



Printing date 02/02/2016 Reviewed on 02/02/2015

Trade name: Premicote FG White

(Contd. of page 7)

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

UN-Number		
DOT, ADN, IMDG, IATA	not regulated	
UN proper shipping name DOT, ADN, IMDG, IATA	not regulated	
Transport hazard class(es)		
DOT, ADN, IMDG, IATA		
Class	not regulated	
Packing group		
DOT, IMDG, IATA	not regulated	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex	II of	
MARPOL73/78 and the IBC Code	Not applicable.	

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Clean Air Act

None of the ingredients is listed.

· Clean Water Act

None of the ingredients is listed.

- Sara
- · SARA 302/304 Extremely Hazardous Substance

None of the ingredients is listed.

(Contd. on page 9)



Reviewed on 02/02/2015

Trade name: Premicote FG White

	(Contd. of pag
Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
Section 313 (Specific toxic chemical listings):	
1897-45-6 chlorothalonil (ISO)	
1336-21-6 ammonia	
1344-28-1 aluminium oxide	
TSCA (Toxic Substances Control Act):	
All ingredients are listed.	
Massachusetts Right To Know	
57-55-6 propane-1,2-diol	
64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic	
64741-88-4 Distillates (petroleum), solvent-refined heavy paraffinic	
1344-28-1 aluminium oxide	
· New Jersey Right To Know	
64741-88-4 Distillates (petroleum), solvent-refined heavy paraffinic	
1344-28-1 aluminium oxide	
Pennsylvania Right To Know	
57-55-6 propane-1,2-diol	
64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic	
64741-88-4 Distillates (petroleum), solvent-refined heavy paraffinic	
1344-28-1 aluminium oxide	
Proposition 65	
Chemicals known to cause cancer:	
13463-67-7 titanium dioxide	
1897-45-6 chlorothalonil (ISO)	
Polycarboxylate, ammonium salt	-
119-61-9 benzophenone	
14808-60-7 Quartz (SiO2)	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
· Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
· Carcinogenic categories	
· EPA (Environmental Protection Agency)	
1314-13-2 zinc oxide	D, I,
· TLV (Threshold Limit Value established by ACGIH)	
13463-67-7 titanium dioxide	
14808-60-7 Quartz (SiO2)	
17000-00-7 [Quartz (StO2)	



Printing date 02/02/2016 Reviewed on 02/02/2015

Trade name: Premicote FG White

(Contd. of page 9)

· NIOSH-Ca (National Institute for Occupational Safety and Health)

13463-67-7 titanium dioxide

14808-60-7 Quartz (SiO2)

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07 GHS

- · Signal word Danger
- · Hazard-determining components of labeling:

titanium dioxide

chlorothalonil (ISO)

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Distillates (petroleum), solvent-refined heavy paraffinic

· Hazard statements

Causes skin and eye irritation.

May cause an allergic skin reaction.

May cause cancer.

· Precautionary statements

In case of inadequate ventilation wear respiratory protection.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves/protective clothing/eye protection/face protection.

Avoid release to the environment.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

In case of fire: Use for extinction: CO2, sand, extinguishing powder.

In case of fire: Use for extinction: Water spray.

IF ON SKIN: Wash with plenty of water.

Collect spillage.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 11)



Printing date 02/02/2016 Reviewed on 02/02/2015

Trade name: Premicote FG White

(Contd. of page 10)

- · National regulations:
- · Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Accella Polyurethane Systems, LLC urges each customer of recipient of this (M)SDS to study it carefully and consult

appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effectivie date shown on this (M)SDS. However, no warranty, express or implied is given. Regulatory reuirements are subject to change and may differ between various locations It is the buyer's/user's responsibility to ensure that his/her activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the produt are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M) SDS, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most curent version.

- · Department issuing SDS: Environmental Health & Safety Department.
- · Contact: M. Phillips
- · Date of preparation / last revision 02/02/2016 / -
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Tox. 4: Acute toxicity, Hazard Category 4

Acute Tox. 2: Acute toxicity, Hazard Category 2

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

 ${\it Eye Dam. 1: Serious \ eye \ damage/eye \ irritation, Hazard \ Category \ 1}$

Eve Irrit. 2B: Serious eve damage/eve irritation, Hazard Category 2B

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 1A: Carcinogenicity, Hazard Category 1A

Carc. 1B: Carcinogenicity, Hazard Category 1B

Carc. 2: Carcinogenicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3