


VentureTape[®] 460 is an embossed vinyl coated with an aggressive acrylic pressure sensitive adhesive. Specifically designed for use as a seaming tape for vinyl faced fiberglass insulation, VentureTape 460 applies easily and excels in demanding temperature and humidity applications, providing superior performance and durability over a wide range of conditions.

Product Construction



Features & Benefits

- Specifically designed for seaming vinyl faced fiberglass insulation
- Bonds securely to its own backing
- High performance seaming tape is ideal for use on vinyl faced fiberglass insulation and water heater blanket insulation
- Acrylic adhesive performs well over a wide temperature range
- Available in 2 color options; black and white

Test	Typical Value	Typical Value (Metric)	Test Method
Product Thickness ^Ω	4.6 mils	0.12 mm	PSTC-133
Peel Adhesion ^Δ	35 oz/in	9.8 N/25 mm	PSTC-101
Shear Adhesion	>24 hrs @ 2.2 psi	>24 hrs @ 15.2 kPa	PSTC-107
Tensile Strength	7 lb/in	31.6 N/25 mm	PSTC-131
Elongation	100 %	100 %	PSTC-131
Service Temperature	-40 to 225 °F	-40 to 107 °C	
Ω - excluding liner		△ - 20 minute dwell	

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Product Configurations

- Available in black and white
- 3" (75 mm) standard width
- Custom widths and lengths available, contact Venture Tape for specifications and requirements

Contact Venture Tape today for a complete list of products or a free sample

Toll Free North America 800-343-1076 From United Kingdom 0-800-962-957 From Australia 1-800-122-797 www.venturetape.com



GTA - NHT, Inc. Venture Tape 30 Commerce Rd., Rockland, MA 02370 Tel 781-331-5900; Fax 781-871-0065 800-343-1076 (U.S.A.), 800-544-1024 (Canada) Toll Free Fax 877-264-5490 www.venturetape.com

